ZEBRA ZT220

Standard Features

• Print Methods: Direct thermal and Thermal Transfer (optional)

• Resolution: 203 dpi



More Standard Features

• Element Energy EqualizerTM (E3®) for superior print quality

• USB 2.0 and RS-232 serial ports

• Dual media sensors - transmissive and reflective sensing technology, selectable through software or front panel

• Media supply hanger designed for 1" (25mm) through 3" (76mm) core diameters

• Side loading metal print mechanism with head open lock

• Link-OSTM environment capable

Printer Specifications

Resolution: 203 dpi (8 dots/mm)

300 dpi (12 dots/mm)

Memory: 128MB Flash, 128MB RAM

Print width: 4.09"/104 mm

Print length: 203 dpi: 157"/3,988 mm and 300dpi: 73"/1854 mm (optional)

Print speed: 203 dpi: 6" (152 mm)/sec

300 dpi:

6" (152 mm)/sec

Media sensors Reflective, Transmissive

Media Characteristics

Maximum label and liner width: 4.50"/114 mm Minimum label and liner width: 0.75" (19.4 mm) Maximum non-continuous label length: 39"/991 mm

Maximum Media Roll Size:

• 8.0" (203 mm) O.D. on a 3" (76 mm) I.D. core

• 6.0" (152 mm) O.D. on a 1" (25 mm) I.D. core

Media thickness: 0.003"/0.076 mm to 0.010"/0.25 mm Media types: continuous, die-cut, notch, black mark

Ribbon Characteristics

Outside diameter: 300m = 2.7"/68.6 mm

Standard length: 984'/300 m

Ribbon width: 1.57"/40 mm to 4.33"/110 mm Ribbon setup: Ribbon wound ink-side out

ID Core: 1.0" (25.4 mm)

Operating Characteristics

Operating temperature TT: Operating temperature: 40° F (5° C) to 104° F (40° C) Thermal transfer DT: Operating temperature: 32° F (0° C) to 104° F (40° C) Direct thermal Storage temperatures: -40° F (-40° C) to 140° F (60° C)

Operating humidity: 20% to 85% non-condensing Storage humidity: 5% to 85% non-condensing

Energy Star certified auto-detectable 90-265VAC, 48-62 Hz, 100 W Power Supply

Agency approvals

- IEC 60950
- EN 55022 Class B
- EN55024
- EN 61000-3-2
- EN 61000-3-3

Physical Characteristics

Width: 9.5"/242 mm Height: 10.9" (277 mm) Depth: 17" (432 mm) Weight: 20 lbs (9.1 kg)

Shipping weight: 25 lbs (11.4 kg)