

CAB printere

Technical data

■ Standard □ Option

	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	1.10	
Label printer	A2+	A4+	A6+	A8+	A4+M	XD4	A4+T	XD4T	XC4	XC6	
Print head											
Print method	Thermal transfer										
	Thermal direct										
Print resolution dpi	300	600	203	300	600	203	300	300	300	300	
Print speed up to mm / s	150	100	250	250	100	200	200	150	125	100	
Print width mm	54,2	57	104	105,6	105,6	168	162,6	216	105,6	105,6	
Material											
Labels, continuous rolls or fanfolded	Paper, cardboard, textile, plastics such as PET, PE, PP, PI, PVC, PU, acrylate										
Material thickness mm / weight g / m ²	0,05 - 0,8 / 60 - 300					0,05 - 0,2 / 60 - 180					
Width labels ¹⁾ mm	4 - 63	20 - 116		46 - 176		46-220	4 - 106	–	4 - 106	–	
continuous material / liner mm	25 - 67	24 - 120		50 - 180		50-235	10 - 110		–		
continuous shrink tube mm	10 - 67	25 - 85		–		–	4 - 85	4 - 85		–	
Height ¹⁾ without back-feed from mm	4	4	4	4	4	6	6	10	5	5	
when dispensing ¹⁾ from mm	12	12	12	12	12	25	25	–	–	–	
up to mm	5000	2000	5000	4000	1000	4000	3000	2000	4000	1000	
Media roll	Outside diameter up to mm										
	205		205		205		205		300		
Core diameter mm	38 - 100									76	
Winding	Outside or inside										
Ribbon											
Ink	Outside or inside										
Roll diameter up to mm	80					72	80	72	80	72	72
Core diameter mm	25					25	25	25	25	25	25
Ribbon length variable up to m	500					360	500	360	500	360	360
Width ²⁾ up to mm	57	114		165		220	114	114	114	114	
Internal rewriter (only for peel-off version)											
Outside diameter up to mm	142					–					
Core diameter mm	38,1					–					
Winding	Only outside					–					
Dimensions Printer											
Height mm	274					395	274	395	395		
Depth mm	446					554	446	554	554		
Width mm	190	242		302	352	242	248	242	248	358	
Weight kg	8,5	9		13	15	9	21	9	21	24	