

## ZEBRA GC420d



### Standard Features

- Print method: direct thermal
  - EPL and ZPL programming languages standard
  - 32 bit RISC processor
- 

### More Standard Features

- Quick and easy ribbon loading system
  - Construction: ABS double-walled casing
  - OpenACCESS™ design
- 

### Printer Specifications

Resolution: 203 dpi (8 dots/mm)  
Memory: Standard: 8 MB SDRAM; 8 MB Flash  
Print width: 4.09" (104 mm) maximum  
Print length: 39" (991 mm) maximum  
Print speed: 4" (102 mm)/sec  
Media sensors: Reflective, Transmissive

---

### Media Characteristics

Maximum label and liner width: 4.25" (108 mm)  
Minimum label and liner width: 1.00" (25.4 mm)  
Maximum label and liner length: 39" (991 mm)  
Maximum roll diameter: 5" (127 mm)  
Core diameter: 1.0" (25.4 mm) and 1.5" (38 mm)  
Media thickness: 0.003" (.08 mm) to 0.007" (0.18 mm)  
Media types: tag stock, Roll or fanfold

---

### Operating Characteristics

Operating temperature

TT: Operating temperature 40° F (5° C) to 105° F (41° C) Thermal transfer  
DT: Operating temperature 40° F (5° C) to 105° F (41° C) Direct thermal

Storage temperatures: -40° F (-40° C) to 140° F (60° C)

Operating humidity: 10-90% non-condensing R.H.

Storage humidity: 5-95% non-condensing R.H.

Electrical: Auto-detecting (PFC compliant) 110-240 VAC, 50-60 Hz

#### Agency approvals

- TUV-R NRTL
- TUV-R CB
- NOM
- KCC
- CE
- FCC Class-B

---

#### Physical Characteristics

Width: 7.9" (201 mm)

Height: 6.7" (170 mm)

Depth: 8.2" (208 mm)

Weight: 3 lbs (1.4 kg)

Orientation: Center